SPRAY SHORT BURSTS
MATERIAL DISCHARGES RAPIDLY

READ DIRECTIONS
FOR BEST RESULTS

Homax®

Ceiling Texture

Textura para techo

POPCORN

Muy rugoso

0.19 m²

2 sq. ft

Professional Match

Casamiento profesional

Vertical Spray
Matches Commercially Applied Popcorn

Rocío vertical
Iguala el tirol aplicado comercialmente

WARNING! CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
Read other cautions on side/back panel before using.
¡PELIGRO! CONTENIDO BAJO PRESIÓN. CAUSA IRRITACIÓN EN LOS OJOS, LA PIEL Y LAS VÍAS RESPIRATORIAS.
Lea otras precauciones en el panel posterior y lateral antes de usar.

Net Wt 16 OZ
(454 g)

WATER BASED

Homax® Professional Match Popcorn Ceiling Texture is the same commercial grade polystyrene chip material used by professionals when popcorn ceiling is originally applied. Use to patch and repair popcorn ceiling texture, or apply new texture to small areas.

La textura para techos casamiento profesional Homax® consta del mismo material de fragmentos de poliestireno de calidad comercial que los profesionales usan cuando aplican techos muy rugosos. Úselo para reparar y cubrir acabados para techos muy rugosos dañados o para aplicar nuevo acabado sobre áreas pequeñas.

SEE ONLINE DEMO at www.homaxpro.custhelp.com/textures

PROTECT CARPET, FURNITURE AND WALLS FROM OVERSPRAY.
TIP: Pin up plastic drape or hold a box around patch area to contain overspray.

- Water-based, use warm water for clean up.
- Sprays best between 68° F and 72° F.
- Eye protection recommended.
- DO NOT spray sideways or upside down.
- DO NOT clear nozzle or test product by spraying upside down.
- DO NOT hold nozzle down for more than 1 second.

DIRECTIONS FOR USE: MAKE ANY NECESSARY CEILING REPAIRS BEFORE APPLYING. PRIME/SEAL AREA WHITE BEFORE APPLYING TEXTURE.

1. Shake can vigorously for one minute.
2. Screw nozzle onto valve stem.
3. Place fingers on either side of the spray nozzle and hold approximately 9-14" from ceiling surface.
4. To spray, quickly trigger nozzle in half second bursts, releasing the nozzle after each pass. Use short, sweeping strokes, feathering texture into surrounding area. If nozzle is held down continuously propellant will be released in 2 to 4 seconds leaving unused material in can. Proper technique allows for 8 to 10 short application strokes.

DRY TIME: Allow texture to dry 24 hours if painting over is desired.
TIP: For a heavier "chip" appearance apply in multiple thin coats, allowing texture to dry slightly between applications. Do not apply too heavily or texture will drip or sag.

PROTEJA LAS ALFOMBRAS, MUEBLES Y PAREDES DEL EXCESO DE CHORRO.
CONSEJO: Coloque una cortina de plástico o sostenga una caja alrededor de la zona que se va a cubrir para que retenga el exceso de chorro.

- La textura es a base de agua, utilice agua tibia para la limpieza.
- Se rocía mejor entre 20 °C y 22,2 °C.
- NO dirija el chorro de arriba abajo para limpiar la boquilla o para probar el producto.
- NO mantenga presionada la boquilla por más de un segundo.
- Se recomienda el uso de lentes de protección.

INSTRUCCIONES DE USO: ANTES DE LA APLICACIÓN, REPARE EL TECHO SEGÚN SEA NECESARIO. APLIQUE PINTURA BASE O SELLE EL ÁREA DE BLANCO ANTES DE APLICAR LA TEXTURA.

1. Agite la lata vigorosamente durante un minuto.
2. Enrosque la boquilla en el vástago de la válvula.
3. Coloque los dedos en uno de los lados de la boquilla del chorro y sosténgalo a una distancia de entre 20,86 cm y 35,56 cm aproximadamente de la superficie del techo.
4. Para que salga el chorro, presione rápidamente la boquilla con toques de medio segundo y suéltela después de cada pasada. Use movimientos cortos y de barrido para alisar la textura en el área circundante. Si mantiene presionada la boquilla continuamente, el propelente se saldrá en 2 a 4 segundos y dejará el material sin usar dentro de la lata. Una técnica adecuada permite de 8 a 10 movimientos cortos de aplicación.

TIEMPO DE SECADO: Si desea pintar, deje que la textura seque durante 24 horas.
CONSEJO: Para un acabado aún más rugoso, aplique muchas capas gruesas y deje que el acabado seque ligeramente entre cada aplicación. No aplique demasiado o el acabado goteará o se doblará.

Para ver todos los advertencias en español, visite

WARNING! CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. Read other cautions on side/back panel before using. Contains Calcium Carbonate, Clay, Perlite, Titanium Dioxide and Nitrogen (propellant). Store upright in a cool, dry place. Avoid prolonged exposure to sunlight and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Use with adequate ventilation. Avoid breathing spray mist. Avoid contact with eyes and skin. Wear safety glasses or goggles. Wash hands after using. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If inhaled, remove person to fresh air. If breathing does not improve, get medical attention. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the State of California to cause cancer. **WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **ASBESTOS WARNING:** If your ceiling texture was applied prior to 1979, DO NOT attempt to remove it without having it tested for asbestos content. Contact your local EPA office or log on to www.epa.gov/asbestos for information.

Flat Paint Product_VOC < 50% MIR <1.20
This product is covered by one or more U.S. Patents.

Homax® A Premier Brand of
The Homax Group, Inc.
Bellingham WA 98227
www.homaxproducts.com
800-729-0029
MADE IN USA

0 41072 04070 9

0 41072 04070 9